



ASP 4-6.5kW

Split/Single-Phase Off-grid Solar Storage Inverter

- Used with 48V energy storage battery
- Two efficient independent MPPT ports are available
- Two output modes, mains bypass output and inverter output, provide uninterrupted power supply
- Support time-sharing charge and discharge function
- Support 6 parallel machines up to 39kW



ABOUT SRNE

- SRNE 16 years in PV industry, committed to independent R&D and production.
- Holds over 200 patents in energy storage, with unique industry-leading technologies.
- Chooses top-quality international components to deliver high-value products to customers.
- Upholds values of customer priority, proactivity, responsibility, and innovative breakthroughs.

Model	ASP4840U100-H	ASP4850U120-H	ASP4860U140-H	ASP4865U140-H
INVERTER OUTPUT				
Rated Output Power	4,000W	5,000W	6,000W	6,500W
Max. Output Power	8,000VA	10,000VA	12,000VA	13,000VA
Rated Output Voltage	120Vac, single-phase/240Vac, split-phase			
Rated Frequency	50/60Hz			
Waveform	Pure sine wave			
Switch Time	10ms (typical)			
BATTERY				
Battery Type	Lithium-ion battery/lead-acid battery/user-defined battery			
Rated Battery Voltage	48V			
Battery Voltage Range	40~60Vdc			
Max. Grid/Generator Charging Current	60A	60A	80A	80A
Max. Hybrid Charging Current	100A	120A	140A	140A
SOLAR INPUT				
No. Of MPPT	2			
Max. PV Array Power	3,000W+3,000W	3,800W+3,800W	4,500W+4,500W	5,000W+5,000W
Max. Input Current	18A+18A			
Max. Open Circuit Voltage	550Vdc+550Vdc			
MPPT Voltage Range	150~450Vdc			
GRID/GENERATOR INPUT				
Input Voltage Range	65~140Vac			
Input Frequency Range	50/60Hz			
Bypass Overload Current	40A			
EFFICIENCY				
MPPT Tracking Efficiency	99.9%			
Max. Efficiency	93%			

GENERAL DATA				
Parallel Capacity	1~6 Units (More than 3 units in parallel can form a three-phase output)			
Dimension	584.6mm*410mm*133mm	Noise	<60dB	
Weight	18.9kg	Cooling Method	Intelligent fan	
Protection Degree	IP20 Indoor Only	Warranty	2 years	
Temperature	-10~55°C, >45°C Derate	Communication	RS485/CAN/USB/Dry Contact	
External Module (Optional)	Wi-Fi/GPRS			
Certificate	RoHs/EN61000-6-1/EC61000-6-3/FCC Part15 ClassB/IEC62109-1/IEC62109-2/UL1741			

PROTECTION

Has PV input current limiting protection, PV input over-voltage, PV night reverse current protection, AC input over-voltage protection, AC input under-voltage protection, Battery over-voltage protection, Battery under-voltage protection, Battery over-current protection, AC output short-circuit protection, Heat sink over-temperature protection, Inverter over-load protection.