

# Growatt SPF 3000TL LVM

- Integrated MPPT charge controller
- Configurable grid or solar input priority
- Optional WIFI/ GPRS remote monitoring
- Parallel for scalability



P O W E R  
- I N G  
T O M O R R O W  
R R O W

**Growatt**  
powering tomorrow

[www.ginverter.com](http://www.ginverter.com)

Datasheet	SPF 3000TL LVM-24P	SPF 3000TL LVM-48P
Battery voltage	24VDC	48VDC

#### INVERTER OUTPUT

RATED POWER	3000VA/ 3000W	3000VA/ 3000W
Parallel Capability	Yes	Yes
AC Voltage Regulation (Battery Mode)	120VAC $\pm$ 5% @ 50/60Hz	120VAC $\pm$ 5% @ 50/60Hz
Surge Power	6000VA	6000VA
Efficiency (Peak)	93%	93%
Waveform	Pure sine wave	Pure sine wave
Transfer Time	10 ms (For Personal Computers); 20 ms (For Home Appliances)	10 ms (For Personal Computers); 20 ms (For Home Appliances)

#### SOLAR CHARGER

Maximum PV Array Power	2000W	4500W
MPPT Range @ Operating Voltage	30VDC ~ 115VDC	60VDC ~ 115VDC
Maximum PV Array Open Circuit Voltage	145VDC	145VDC
Maximum Solar Charge Current	80A	80A
Maximum Efficiency	98%	98%
Standby Power Consumption	2 W	2 W

#### AC CHARGER

Charge Current	60A	40A
AC Input Voltage	120 VAC	120 VAC
Selectable Voltage Range	95-140 VAC (For Personal Computers) ; 65-140 VAC (For Home Appliances)	95-140 VAC (For Personal Computers) ; 65-140 VAC (For Home Appliances)
Frequency Range	50Hz/60Hz (Auto sensing)	50Hz/60Hz (Auto sensing)

#### PHYSICAL

Dimension (D/W/H) in mm	130/350/455	130/350/455
Net Weight (kgs)	11.5	11.5

#### OPERATING ENVIRONMENT

Humidity	5% to 95% Relative Humidity(Non-condensing)	5% to 95% Relative Humidity(Non-condensing)
Operating Temperature	0°C - 55°C	0°C - 55°C
Storage Temperature	-15°C - 60°C	-15°C - 60°C