




► Overview

DC connector MD-MC4 series are applicable for use in connection for photovoltaic devices like DC combiner box, Inverters, String Combiner Boxes, etc ,double electric shock free protection for load closure and disconnection,can meet quick connection and anti vibration function. rainproof,moisture-proof,dust-proof and durable .waterproof grade IP67.high heat resistance,wear resistance,durability, corrosion resistance, thick copper inner core,high quality material selection.

► Technical data

Connector system	Φ4mm
Rated voltage	1000V DC(IEC)
Rated current	17A,22A,30A(1.5mm²,2.5mm²; 14AWG,4mm²; 6mm²; 12AWG,10AWG)
Test voltage	6kV(50Hz,1min.)
Temperature Range	-40°C...+90°C(IEC) -40°C...+75°C(UL)
Upper Temperature Limit	+105°C (IEC)
Degree of protection,mated	IP67
unmated	IP2X
Contact resistance of plug connectors	0.5mΩ
Safety class	II
Contact material	Messing,verzinkt Copper Alloy,tin plated
Insulation material	PC/PPO
Locking system	Snap-in
Flame class	UL-94-V0
Salt mist spray test,degree of severity 5	IEC 60068-2-52

► Dimensions(mm)



► Overview

DC connector MD-MC4 series are applicable for use in connection for photovoltaic devices like DC combiner box, Inverters, String Combiner Boxes, etc ,double electric shock free protection for load closure and disconnection,can meet quick connection and anti vibration function. rainproof,moisture-proof,dust-proof and durable .waterproof grade IP67.high heat resistance,wear resistance,durability, corrosion resistance, thick copper inner core,high quality material selection

► Technical data

Connector system	Φ4mm
Rated voltage	1500V DC(IEC) ¹
Rated current	17A,22A,30A,45A(1.5mm²,2.5mm²; 14AWG,4mm²; 6mm²; 12AWG,10AWG)
Test voltage	6kV(50Hz,1min.)
Temperature Range	-40°C...+90°C(IEC)-40°C...+75°C(UL)
Upper Temperature Limit	+105°C(IEC)
Degree of protection,mated	IP67
unmated	IP2X
Contact resistance of plug connectors	0.5mΩ
Safety class	II
Contact material	Messing,verzinkt Copper Alloy,tin plated
Insulation material	PC/PV
Locking system	Snap-in
Flame class	UL-94-V0
Salt mist spray test,degree of severity 5	IEC 60068-2-52

► Dimensions(mm)

